

FREE WEIGHT AREAS



TECHNICAL DATA SHEET

PAVIGYM
THE BASIS OF FITNESS

P PAVIGYM
ENDURANCE S&S

Extra-thickness for more protection
against impacts for heavy loads.


TECHNICAL INFORMATION

Weight		16 kg
Density	UNE-53526	900 kg/m ³
Hardness	din 53505	75° Shore A
% water absorption	ASTM D570	0%
Coef. linear dilatation	0°C-40°C	10 ⁻⁴ °C ⁻¹
Fire classification	EN 13501-1	Cfl-s1
Formaldehyde emission	EN 717-2	<0,5
Sound insulation	ISO 10140	21 dB

COMPARATIVE CHART

	PAVIGYM ENDURANCE S&S	PAVIGYM ENDURANCE	RECYCLED RUBBER (ROLLS)
Comfort	*****	***	**
Marks resistance (medium loads)	*****	****	***
Marks resistance (heavy loads)	****	***	**
Sound insulation	*****	***	**
Durability	*****	****	***
Hygienic / Anti-bacterial protection	*****	*****	**
Thermal insulation	*****	*****	***
Water resistance	*****	*****	***
Easy to install & maintain	*****	*****	**


COLOURS



PAVIGYM WENGUE




PAVIGYM BEECHWOOD



PAVIGYM STONE GREY



PAVIGYM B. MARBLE



PAVIGYM JET BLACK


**The appearance and color of these pictures may differ slightly from the final product.*

SPECIAL COLOURS

**Contact us for more info about availability.*



PAVIGYM CYAN



PAVIGYM LIME



PAVIGYM RED




PAVIGYM WALNUT



INTERLOCKING SYSTEM

To avoid product counterfeiting, our tiles are marked with the Pavigym logo



THICKNESS 22 mm



Top Layer
Virgin rubber = resistance and friction

Bottom Layer
Rubber + air = Impact absorption + sound absorption



TOP LAYER VIRGIN RUBBER

FREE WEIGHT AREAS

PAVIGYM
ENDURANCE S&S

