

GROUP-X ACTIVITIES



PAVIGYM
THE BASIS OF FITNESS



DATASHEET

P PAVIGYM
MOTION

The unique solution for aerobic and group-x areas



An industry first: one flooring that meets all requirements. Reduction of injuries, shock absorption and point elasticity, friction specially for group-x and avoid marks on the floor.


TECHNICAL INFO

Weight		7 kg
Density	UNE-53526	860 kg/m ³
Hardness	DIN 53505	75° Sh A
Water absorption	ASTM D570	0%
Coef. of linear dilatation	0°C-40°C	1,5 10 ⁻⁴⁰ C ⁻¹
Fire reaction	EN 13501-1	Cfl-s2
Abrasion resistance	EN-5470	614 mg
Shock absorbance	EN 14808	30%
Coefficient of friction	EN 13036	95


COMPARATIVE CHART

	PAVIGYM MOTION	WOODEN SPRING	LINOLEUM (PVC)
Comfort and wellness	*****	***	***
Shock absorption	****	**	****
Movement protection (Slip/blocking)	****	***	***
Sound insulation	****	**	***
Thermal insulation	****	****	****
Durability	*****	***	**
Water resistance	*****	**	****
Easiness and short installation time	*****	**	***
Damaged area replacement (modularity)	*****	*	*

COLOURS



PAVIGYM WENGUE




PAVIGYM BEECHWOOD



PAVIGYM STONE GREY



PAVIGYM B. MARBLE




PAVIGYM JET BLACK

**The appearance and color of these pictures may differ slightly from the final product.*

SPECIAL COLOURS *On request: min. quantities of 70m²




PAVIGYM CYAN



PAVIGYM LIME



PAVIGYM RED




PAVIGYM WALNUT



INTERLOCKING SYSTEM

To avoid counterfeiting, our tiles are marked with the Pavigym logo.



THICKNESS 9 mm



3 mm Top Layer

Virgin rubber + Pavigym friction compounds = Resistance + Optimized friction

6 mm Bottom Layer

Rubber + Air (Pavigym Air Flooring System) = Impact absorption + Energy return

GROUP-X ACTIVITIES

P PAVIGYM
MOTION

